

Rx32


- 3-way compact versatile full range system
- Light weight, very high power of 800 W
- Unique 2" coaxial neodymium driver
- Neodymium 12" ultra low distortion woofer
- Passive or Bi-amplified operation
- Designed for fixed installation and touring




Applications:

Theatre
Corporate Events
Club
Stage Monitor
Band PA

The Coda Audio Rx32 is a versatile, full range, 3-way loudspeaker system that features a high power 12" neodymium cone driver and a 2" coaxial neodymium driver coupled to a 90° x 55° waveguide. As a 3-way system, the Rx32 may be driven passively or with bi-amplification to provide extremely high acoustic output. The Rx32 incorporates a multidesign enclosure fitted with M6 threaded points for use with an optional U-bracket and includes an integral top hat. Integrated air cargo flying tracks enable easy suspension for both fixed installation using M6 eyebolts or touring applications using clip-on cargo spring stud.



U-bracket
vertical



U-bracket
horizontal



24481
Wall mount



68620
Truss clamp

TECHNICAL SPECIFICATIONS:

■	3-way full range multi design
Application:	High level short/medium throw or stage monitor
Frequency response:	60 Hz - 21k Hz (- 3 dB)
Power handling AES:	800 W
Peak power:	3000 W
Sensitivity:	99 dB
Max. SPL peak:	134 dB
Dispersion:	90° x 55°
Components:	
■	12" neodymium woofer
	4" (101.6 mm) voice coil, 750 W (AES)
High frequency:	2" neodymium coaxial driver
	3.5" (90 mm) + 1.75" (44.4 mm) VC, 150 W + 80 W
Crossover:	800 Hz, 6.3 kHz Passive
Nominal impedance:	8 Ohm
Input connectors:	2 x Neutrik™ NL4MP
Suspension:	2 x air cargo tracks and 8 x M6 treaded points
Enclosure material:	15 mm plywood
Finish:	textured black paint
Dimensions:	348 x 594 x 320 mm
Net weight:	20 kg